


## SMD ■ B

## 23-22C/S2ST3D-C30/2A

**Features**

- Package in 8mm tape on 7" diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Multi-color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.
- Compliance with EU REACH
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

**Description**

- The 23-22C SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.
- Besides, lightweight makes them ideal for miniature applications. etc.

**Applications**

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.

## Device Selection Guide

Chip Type	Chip Materials	Emitted Color	Resin Color
S2S	AlGaInP	Brilliant Orange	Yellow Diffused
T3	InGaN	Pure White	

## Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Reverse Voltage	$V_R$	5	V
Forward Current	$I_F$	S2S : 50 T3 : 10	mA
Peak Forward Current (Duty 1/10 @1KHz)	$I_{FP}$	S2S : 100 T3 : 100	mA
Power Dissipation	$P_d$	S2S : 120 T3 : 40	mW
Operating Temperature	$T_{opr}$	-40 ~ +85	°C
Storage Temperature	$T_{stg}$	-40 ~ +90	°C
Electrostatic Discharge	$ESD_{HBM}$	S2S : 2000 T3 : 150	V
Soldering Temperature	$T_{sol}$	Reflow Soldering : 260 °C for 10 sec. Hand Soldering : 350 °C for 3 sec.	

## Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	$I_v$	S2S : 18.0 T3 : 45.0	-----	45.0 112	mcd	$I_F=5mA$
Viewing Angle	$2\theta_{1/2}$	-----	140	-----	deg	
Peak Wavelength	$\lambda_p$	S2S : ----- T3 : -----	611	-----	nm	
Dominant Wavelength	$\lambda_d$	S2S : ----- T3 : -----	605	-----	nm	
Spectrum Radiation Bandwidth	$\Delta\lambda$	S2S : ----- T3 : -----	17	-----	nm	
Forward Voltage	$V_F$	S2S : 1.7 T3 : 2.7	-----	2.4 3.7	V	$V_R=5V$
Reverse Current	$I_R$	S2S : ----- T3 : -----	-----	10 50	μA	

Note:

Tolerance of Luminous Intensity: ±11%

## Bin Range of Luminous Intensity S2S

Bin Code	Min.	Max.	Unit	Condition
M	18.0	28.5	mcd	$I_F = 5\text{mA}$
N	28.5	45.0		

## T3

Bin Code	Min.	Max.	Unit	Condition
P	45.0	72.0	mcd	$I_F = 5\text{mA}$
Q	72.0	112		

Note:

Tolerance of Luminous Intensity:  $\pm 11\%$

EVERLIGHT

## Chromaticity Coordinates Specifications for Bin Grading

Bin Code	CIE_x	CIE_y	Condition
1	0.274	0.226	I <sub>F</sub> =5mA
	0.274	0.258	
	0.294	0.286	
	0.294	0.254	
2	0.274	0.258	
	0.274	0.291	
	0.294	0.319	
	0.294	0.286	
3	0.294	0.254	
	0.294	0.286	
	0.314	0.315	
	0.314	0.282	
4	0.294	0.286	
	0.294	0.319	
	0.314	0.347	
	0.314	0.315	







### Notes:

- 1.The C.I.E. 1931 chromaticity diagram ( Tolerance  $\pm 0.01$  ).
- 2.The products are sensitive to static electricity and care must be fully taken when handling products.







The graph displays a function  $y = 0.0001x^4 - 0.0004x^3 + 0.0012x^2 - 0.0008x + 0.6$ . The x-axis ranges from 0 to 0.8, and the y-axis ranges from 0 to 0.9. The curve starts at approximately (0, 0.6), reaches a peak at (0.1, 0.84), and then decreases, passing through points labeled 400 to 750. A rectangular region is highlighted with points 1, 2, 3, and 4. The points are labeled as follows:

- 400: (0.18, 0.00)
- 410: (0.19, 0.01)
- 420: (0.20, 0.02)
- 430: (0.21, 0.03)
- 440: (0.22, 0.04)
- 450: (0.23, 0.05)
- 460: (0.24, 0.06)
- 470: (0.25, 0.07)
- 480: (0.26, 0.08)
- 490: (0.27, 0.09)
- 500: (0.28, 0.10)
- 510: (0.29, 0.11)
- 520: (0.30, 0.12)
- 530: (0.31, 0.13)
- 540: (0.32, 0.14)
- 550: (0.33, 0.15)
- 560: (0.34, 0.16)
- 570: (0.35, 0.17)
- 580: (0.36, 0.18)
- 590: (0.37, 0.19)
- 600: (0.38, 0.20)
- 610: (0.39, 0.21)
- 620: (0.40, 0.22)
- 630: (0.41, 0.23)
- 640: (0.42, 0.24)
- 650: (0.43, 0.25)
- 660: (0.44, 0.26)
- 670: (0.45, 0.27)
- 680: (0.46, 0.28)
- 690: (0.47, 0.29)
- 700: (0.48, 0.30)
- 710: (0.49, 0.31)
- 720: (0.50, 0.32)
- 730: (0.51, 0.33)
- 740: (0.52, 0.34)
- 750: (0.53, 0.35)


## Typical Electro-Optical Characteristics Curves S2S



# Typical Electro-Optical Characteristics Curves T3



## Package Outline Dimensions



Suggested pad dimension is just for reference only.  
Please modify the pad dimension based on individual need.

Note: Tolerances unless mentioned  $\pm 0.1$ mm. Unit = mm



## Moisture Resistant Packing Materials Label Explanation



CPN: XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX

P/N: XXXXXXXXXXXX

XXXXXXXXXX-XXXXXXXXXX-XXXXXXXXXX-XXXXXX

LOT NO: Y150716XXX-XXXXXXXXXX-XXXXXXXXXX

QTY: 0123456789 HUE: XXXXXXXXXXXX

CAT: XXXXXXXXXXXX REF: XXXXXXXXXXXX


REFERENCE: BTPYYMDDXXXXX

MSL-X MADE IN XXXXXX




- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Chromaticity Coordinates & Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number

## Reel Dimensions




Note: The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

## Carrier Tape Dimensions: Loaded quantity 2000 PCS per reel



**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

## Moisture Resistant Packaging



## Precautions For Use

### 1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change ( Burn out will happen ).

### 2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 Before opening the package: The LEDs should be kept at 30℃ or less and 90%RH or less.

2.3 After opening the package: The LED's floor life is 1 year under 30℃ or less and 60% RH or less.


If unused LEDs remain, it should be stored in moisture proof packages.

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment : 60±5℃ for 24 hours.

### 3. Soldering Condition

#### 3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.


3.4 After soldering, do not warp the circuit board.

### 4. Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350℃ for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

### 5. Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



## Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact Everlight before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

EVERLIGHT

## DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.

EVERLIGHT